

TORQUE SPECIFICATIONS

Components	English	Metric
Anti-lock wheel speed sensor	40-60 inch lbs.	5-7 Nm
Axle housing cover bolts	28-35 ft. lbs.	38-47 Nm
Axle housing drain plug	15-30 ft. lbs.	20-41 Nm
Driveshaft retaining bolts	71-95 ft. lbs.	90-130 Nm
Lower rear control arms-to-axle housing nuts and bolts	103-133 ft. lbs.	140-180 Nm
Manual control lever-to-TR/MLP sensor	22-26 ft. lbs.	30-35 Nm
Manual lever positioning switch/TR sensor retaining bolts	80-100 inch lbs.	9-11 Nm
Neutral safety switch	8-11 ft. lbs.	11-15 Nm
Pinion nut	160 ft. lbs.	217 Nm
Pinion shaft lockbolt	15-30 ft. lbs.	20-41 Nm
Shift lever adjusting bolt		
1989 models	14-23 ft. lbs.	19-31 Nm
1990-92 models	10-18 ft. lbs.	13-25 Nm
Torque converter drain plug	21-23 ft. lbs.	28-30 Nm
Torque converter-to-flexplate nuts	20-34 ft. lbs.	27-46 Nm
Transmission-to-engine attaching bolts	40-50 ft. lbs.	55-68 Nm
Transmission pan retaining bolts	107-119 inch lbs.	12-14 Nm
Upper rear control arms-to-axle housing nuts and bolts	103-133 ft. lbs.	140-180 Nm