

SERVICE SPECIFICATIONS

SERVICE DATA

Pedal height from floor panel	157.5 mm (6.201 in.)
Pedal height from asphalt sheet (2WD)	151.4 mm (6.08 in.)
Pedal height from asphalt sheet (4WD)	151.5 mm (5.97 in.)
Push rod play at pedal top	1.0–5.0 mm (0.039–0.197 in.)
Pedal freeplay	5.0–15.0 mm (0.197–0.591 in.)
Clutch release point from pedal full stroke and position	25 mm (0.98 in.) or more
Disc rivet head depth (Minimum)	0.3 mm (0.012 in.)
Disc runout (Maximum)	0.8 mm (0.031 in.)
Diaphragm spring tip non-alignment (Maximum)	0.5 mm (0.020 in.)
Diaphragm spring finger wear (Maximum depth)	0.6 mm (0.024 in.)
Diaphragm spring finger wear (Maximum width)	5.0 mm (0.197 in.)
Flywheel runout (Maximum)	0.1 mm (0.004 in.)

TORQUE SPECIFICATIONS

Part tightened	N·m	kgf·cm	ft·lbf
Clutch line union	15	155	11
Master cylinder installation nut	13	130	9
Bleeder plug	11	110	8
Clutch cover X Flywheel	19	195	14
Release cylinder installation bolt	12	120	9
Release fork support 3VZ-E	47	480	35
22R-E	39	400	29