

# SERVICE SPECIFICATIONS

## SERVICE DATA

|                   |                                  |           |                              |
|-------------------|----------------------------------|-----------|------------------------------|
| Spark plug        | Type                             | ND<br>NGK | W16EXR-U<br>BPR5EY           |
|                   | Gap                              |           | 0.8 mm<br>0.031 in.          |
| High-tension cord | Resistance                       | Limit     | 25 k $\Omega$ per cord       |
| Ignition coil     | Primary coil resistance (Cold)   |           | 0.36–0.55 $\Omega$           |
|                   | Primary coil resistance (Hot)    |           | 0.45–0.65 $\Omega$           |
|                   | Secondary coil resistance (Cold) |           | 9.0–15.4 k $\Omega$          |
|                   | Secondary coil resistance (Hot)  |           | 11.4–18.1 k $\Omega$         |
| Distributor       | Air gap                          |           | 0.2–0.4 mm (0.008–0.016 in.) |
|                   | Pickup coil resistance (Cold)    |           | 185–275 $\Omega$             |
|                   | Pickup coil resistance (Hot)     |           | 240–325 $\Omega$             |

## TORQUE SPECIFICATIONS

| Part tightened              | N·m | kgf·cm | ft·lbf |
|-----------------------------|-----|--------|--------|
| Spark plug X Cylinder head  | 18  | 180    | 13     |
| Distributor X Cylinder head | 19  | 195    | 14     |