























# PREPARATION

## SST (SPECIAL SERVICE TOOLS)

	09308-10010 Oil Seal Puller	
	09330-00021 Companion Flange Holding Tool	
	09504-00011 Differential Side Bearing Adjusting Nut Wrench	
	09506-30012 Differential Drive Pinion Rear Bearing Cone Replacer	
	09550-10012 Replacer Set "B"	
	(09252-10010) No. 1 Replacer Handle	
	(09557-10010) Differential Drive Pinion Front Bearing Replacer	
	(09558-10010) Rear Axle Shaft Oil Seal Replacer	
	09554-30011 Differential Oil Seal Replacer	
	09556-30010 Drive Pinion Front Bearing Remover	
	09557-22022 Companion Flange Remover & Replacer	
	(09557-22030) No. 1 Bolt	
	(09557-22050) No. 3 Bolt	

	09608-35014 Axle Hub & Drive Pinion Bearing Tool Set	
	(09608-06020) Handle	
	(09608-06110) Front Hub Inner & Drive Pinion Front Bearing Cup Replacer	
	(09608-06120) Front Hub Outer Bearing Cup Replacer	
	(09608-06180) Drive Pinion Rear Bearing Cup Replacer	
	09950-00020 Bearing Remover	
	09950-20017 Universal Puller	

## RECOMMENDED TOOLS

	09025-00010 Small Torque Wrench	
	09031-00030 Pin Punch	

## EQUIPMENT

Dial indicator or dial indicator with magnetic base	
Micrometer	
Torque wrench	

## LUBRICANT

Item	Capacity	Classification
Differential oil	7.5 in. 1.35 liters (1.43 US qts, 1.19 Imp. qts) 2WD 8 in. 2 pinion 1.8 liters (1.9 US qts, 1.6 Imp. qts) Others 2.2 liters (2.3 US qts, 1.9 Imp. qts)	API GL-5 Hypoid gear oil SAE 90 SAE 80W or 80W-90